


## Physical Specifications

<b>Packed Dimensions:</b>	<b>W</b>	<b>H</b>	<b>D</b>	
	575mm 22.64"	210mm 8.27"	640mm 25.2"	
<b>Unit Dimensions:</b>	<b>W</b>	<b>H</b>	<b>D</b>	
	430mm 16.93"	88mm 3.5"	495mm 19.48"	
<b>Unit + Rack Handles</b>			<b>D</b>	
			520mm 20.5"	
<b>Rack Depth:</b>			<b>D</b>	
			485mm 19.09"	
<b>Unit Weight:</b>		11.9kg	26.3lbs	
<b>Packed Unit Weight:</b>		17kg	37.5lbs	

**Bundled Accessories:**  
Power Cable (IEC UK/EU/US,), 2 × Single Link DP-DVI adaptors, Getting Started Guide.

## Hardware Specifications

<b>Voltage:</b> 100–240V, 50–60Hz	<b>Memory:</b> 8GB DDR3 RAM	<b>Mounting System:</b>
<b>Power Consumption:</b> 350W @ 230V (max)	<b>Environmental Tolerances:</b> Temperature: 5–35°C (40°–95°F) Humidity: 5%–95% (non-condensing) Altitude: 0–8850 ft (0–2700m)	2U 19" rack mount
<b>Operating System:</b> Windows 8.1 Embedded Pro		<b>Audio:</b> On-board Audio or Pro Audio
<b>CPU:</b> Xeon Quad Core 3.7Ghz		<b>Storage:</b> 1 × 80GB SSD (operation system) 1 × 512GB SSD (media storage)

## System Connectivity I/O (\*Optional factory fitted extras)

<b>Video Outputs – Slot A</b> 2 × DisplayPort 1.2 (max 2560 × 1600) (inc. 2 × Single link DP-DVI adaptors) plus: 1 × DVI DualLink for GUI (max 2560 × 1600)	<b>Video Inputs – Slot B*</b> Choose between either of: No capture card fitted (Base unit) or 2 × 3G-SDI or 1 × DVI	<b>Audio In/Out – Slot C*</b> Choose between either of: On-board audio (Base unit) or Pro-Audio (inc. break-out cable) 2 × Balanced XLR in/out 1 × 1/4" Headphones jack ADAT/SPDIF I/O MIDI in/out
--	---	--

## Media File Specifications

**Video Playback:**  
.mov (anim, pjpg, DXV, Hap, Hap Q)  
**Image Formats:** .bmp, .jpg, .png, .tiff, .tga  
**Audio Playback:**  
.wav/.mp3 (44.1kHz, 16-bit, stereo)  
**3D Mesh Format:** .obj

## Support, Updates and Warranties

**Licence subscription package includes:**  
– Free software upgrades for the life of the machine  
– 2 year return to base hardware warranty (plus options to extend warranty length)  
– Free support (via phone or email)

## Notes

– The d3 2x2plus does not feature Genlock. It cannot frame sync across multiple machines.  
– d3 2x2plus cannot be a Slave in a Master/Slave network, nor can it perform Pro-Audio or Pro capture tasks without the optionally fitted d3 specified cards.